



MMATS Procast 15 Dual 4 ohm

Theil/Small	Dual 4 ohm	Dual 2 ohm
Znom=	2.000 ê	N/A
Sd=	0.0808 sqM	N/A
Fi=	21.388 Hz	N/A
Revc=	1.930 ê	N/A
Fo=	22.171 Hz	N/A
Krm=	0.000 mê	N/A
Vas=	269.7010 Litr	N/A
Qms=	9.237	N/A
Xmx=	9.6250 mM	N/A
Kxm=	0.040 mH	N/A
Cms=	290.9120 uM/N	N/A
Qes=	0.280	N/A
Cmx=	9.6250 mM	N/A
Erm=	1.181	N/A
Mms=	177.1430 Gram	N/A
Qts=	0.272	N/A
Exm=	0.631	N/A
Mmd=	163.9366 Gram	N/A
Pmx=	600.000 Wrms	N/A
SPLo	92.453 dB	N/A



Model	Sealed (Net)	Vented (Net)	Port Specs	Port Disp	Woofer Disp
Procast 15	<u>2.0 cu. ft</u>	3.00 cu.ft	35 sq." X 14" Long	.28 cu.ft	.16 cu.ft.

Hole Cutout Diameter	14.064"
Overall Diameter	15 5/8
Mounting Depth	7.125"

**** Enclosure Size is NET Interior Volume, EXCLUDING speaker and port displacement!!**

3" round port equals 7.07 sq. inches

4" round port equals 12.56 sq. inches

6" round port equals 28.26 sq. inches

